

COCKING SYSTEM	Right hand positioned sidelever with an ambidextrous mount to be able to relocate sidelever on left side for lefthanded shooters.
MAGAZINE TYPE	Removable high capacity, easy load. Newly developed deeper lid to accommodate longer length slugs. Maximum ammunition length, 13 mm (0,51") Made in durable injection-moulded POM 21 shot when Cal .177 18 shot when Cal .22 16 shot when Cal .25 13 shot when Cal .30
STOCK	Ambidextrous. Rear Recoilpad adjustable in height, angle, and length of pull. Cheek Piece adjustable in height (ambidextrous mount) Mount for bag rider. Grip Zero-angle grip AR15 mount specifications Fore End Arca-Swiss rail. Length 14,75" M-Lok system® , left and right side. M-Lok style on the bottom side of the stock. Top Accessory Mount with possibilities to mount picatinny rail in five different positions with M-Lok style in each mount position. Barricade Stop in the end of the Fore End Stock and in the start of the Fore End providing the shooter with solid grip when shooting from a barricade or other unconventional shooting positions.

CALIBRE	4,5 (.177) 5,5 (.22) 6,35 (.25) 7,62 (.30)
BARREL	500: FX Superior STX barrel liner. Length 500 mm 600: Superior Heavy STX barrel liner and carbon fibre liner sleeve. Length 600 mm 700: Superior Heavy STX barrel liner and carbon fibre liner sleeve. Length 700 mm

SHOT CAPACITY	<p>500: 4,5 (.177) N/A 5,5 (.22) 112 shots with 15.89 gr pellet at 870 fps 6,35 (.25) 56 shots with 25.39 gr pellet at 880 fps 7,62 (.30) 37 shots with 44.75 gr pellet at 860 fps</p> <p>600: 4,5 (.177) N/A 5,5 (.22) 80 shots with 22 gr hybrid slug at 900 fps 6,35 (.25) 60 shots with 26 gr hybrid slug at 900 fps 7,62 (.30) 35 shots with 44.5 gr hybrid slug at 900 fps</p> <p>700: 4,5 (.177) N/A 5,5 (.22) 90 shots with 22 gr hybrid slug at 900 fps 6,35 (.25) 70 shots with 26 gr hybrid slug at 900 fps 7,62 (.30) 40 shots with 44.5 gr hybrid slug at 900 fps</p>
FILL PRESSURE	Max 250 bar (3625 psi)
SAFETY	Switch style
OPTICS	Picatinny rail with built in 6 MIL/20 MOA angle. Marked with figures on the right side for easy repositioning of optics.
MUZZLE	Built-In Shroud system (variations may occur depending on country).

PRESSURE GAUGE	Dual Angled Gauges: Air tube pressure WIKA Regulator pressure WIKA
TRIGGER	Adjustable Match Trigger Trigger blade can be adjusted in reach, height and rotated to set the blade in an angle.
VELOCITY	N / A

<p>ENERGY</p>	<p>500: 4,5 (.177) N/A 5,5 (.22) up to 95 J – 70 ft/lbs with 34gr slug at 960 fps 6,35 (.25) up to 108 J – 80 ft/lbs with 43.5gr slug at 910 fps 7,62 (.30): up to 150 J – 110 ft/lbs with 64gr slug at 880 fps 600: 4,5 (.177) N/A 5,5 (.22) up to 111 J – 82 ft/lbs with 34 gr pellet at 1040 fps 6,35 (.25) up to 123 J – 91 ft/lbs with 43.5 gr slug at 970 fps 7,62 (.30) up to 176 J – 130 ft/lbs with 64 gr slug at 1020 fps 700: 4,5 (.177) N/A 5,5 (.22) up to 130 J – 96 ft/lbs with 40 gr slug at 1040 fps 6,35 (.25) up to 145 J – 107 ft/lbs with 55.5 gr slug at 930 fps 7,62 (.30) up to 203 J – 150 ft/lbs with 70 gr slug at 982 fps Note: above figures are maximum FAC Power output using tungsten hammer.</p>
<p>AIR CAPACITY</p>	<p>V300 cc air cylinder + eventual plenum volume</p>

AIR CYLINDER	Carbon fibre wrapped air tank, removable
LENGTH	500: 965 mm – 38" 600: 1118 mm – 44" 700: 1245 mm – 49"
WEIGHT	500: 3,5 kg – 7,65 lbs 600: 3,7 kg – 8,10 lbs 700: 3,9 kg – 8,55 lbs
CHARGING	Rear Foster Quick Disconnect, dust cap included.
MORE FEATURES	AMP MkII Regulator Externally Adjustable Quick Tune System Micro and macro adjustment of hammer spring tension
PLENUM	Micro Plenum – Sub 12ft/lb rifles Macro Plenum – 62 cc Magnum XL Plenum – 156 cc 500: Macro (micro for sub 12ft/lb) 600: Magnum XL 700: Magnum XL